



Product Leaflet

712-112B - MINI M/S FINGER ACT.SPDT GOLD PL /B

Description

Miniature Micro Switches. In SPDT and DPDT versions. With choice of Gold or Silver plated contacts and in different types of Actuating mechanisms.

Specifications

- Electrical
 - Current Rating - 5 Ampere
 - Voltage - 250 V AC
 - Contact Resistance - 30 m ohms max
 - Insulation Resistance - 10 M ohms @ 500 V DC
 - Di-electric withstanding (for 1 min) - 1.0 KV
- Climate
 - - 40 to + 80 degrees Celsius -
- Reference Standard
 - JSS 51204 -
- Usage
 - Defence, Telecommunication, Machinery, Control Panels, Elevators, Cranes and Hoists
- Life
 - Endurance at rated current @ room temperature - 50000 cycles
- Mechanical
 - Chassis mounting -
 - Panel Mounting with Finger and Thumb Actuators - 12 mm Bush
 - Operating Force - 650 gms max
 - Release Force - 55 gms min
 - Pre-travel - 1.5 mm Max
 - Over travel - 0.3 mm min
 - Movement differential - 0.9 mm max

Disclaimer : The Specifications mentioned are subject to change and are not binding on us.
Please reconfirm with us for the latest specifications.