

A-P

FLAT PIN TERMINAL, FOR COPPER CONDUCTORS



Features

TECHNICAL INFORMATION

Minimum operating temperature	-50 °C
Maximum operating temperature	150 °C
Bend angle of the connection	0 °
Markings found	marchio di fabbrica
Type	singolo
Easy insertion input	No
Barrel type	chiuso
Grease inside the barrel	No
Filler putty	No

WEIGHT AND DIMENSIONS

Tip type	flat
----------	------

CLASSIFICATION AND DATA ORDERING


ETIM Class 7	Solderless copper terminals for copper conductors [EC001052]
--------------	--

MATERIAL COMPOSITION AND TREATMENTS

Conductor body material	Electrolitic copper with purity above 99,95%
Minimum thickness of the surface coating of the conducting body	3 μm
Surface treatment of the conductor body	tin plating
Annealing	Yes
Internal surface of the barrel	knurled
Brazed seam	Yes

LOGISTIC

Type of packaging	; box
Customs code	85369010



A-P

tipo	B [mm]	P [mm]	X [mm]	Range of cable cross section [mm²]	L [mm]	Gross weight [g]	A [mm]	Ø [mm]	Cable stripping length [mm]	Ø1 [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	Minimum order quantity [pce]
A2- P12	4.3	14.5	2.2	10	23.5	2,671	9	4.8	9.9	6.8	100	1,500	100
A3- P14	5.5	18	2.2	16	28	3,915	10	5.9	11	7.9	100	1,000	100
A5- P16	7	20.3	2.4	25	32	6,118	11.7	7	12.9	9.3	100	500	100
A7- P20	8	24.5	3		39	10,600	14	8.9	15.4	11.7	100	500	100
A10- P25	9.5	26			45	19,088	19	10	20.9		50	250	50
A14- P30	11	31			55	29,775	24	11.5	26.4		50	200	50