


BATTERY-POWERED HYDRAULIC WIRE ROPE CUTTER, BI-LINEAR, FOR CONDUCTORS AND ROPES IN COPPER, ALUMINUM, ALDREY, STEEL AND ALUMINUM-STEEL WITH MAX Ø 25MM



INCLUDED INTO PACKAGE

ASC55-EU: --

CB1820L: Li-Ion high power battery

CERTIFICATIONS & APPROVALS

 CE |  UKCA

Features

TECHNICAL INFORMATION

Range of operating temperature	-15 ÷ 50 °C
Supply voltage	18 V
Remaining charge indicator	Yes
Software	Yes
Pressure control system	max pressure valve
Equivalent continuous sound pressure	68.5 dBA
Maximum instantaneous sound pressure	87.3 dBC
Acoustic power	75.2 dBA
Standard cycle vibrations	1.015 m/s ²

LOGISTIC

Unit in standard packaging	1 PCE
Minimum order quantity	1 PCE

COMPATIBILITY

Supply CB1820L battery; ASC55-EU battery charger; USB cable; VAL-P22
configuration plastic case; shoulder strap

WEIGHT AND DIMENSIONS

Width	79 mm
Height	401 mm
Maximum height	401 mm
Length	126 mm
Maximum length	126 mm
Maximum aperture	25 mm
Net weight in operation	3.5 kg

CLASSIFICATION AND DATA ORDERING

ETIM Class 7

Cable shears [EC000142]