

KE

END SLEEVE, NON-INSULATED, FOR FLEXIBLE COPPER CONDUCTORS



Features

TECHNICAL INFORMATION

Minimum operating temperature	-50 °C
Maximum operating temperature	150 °C
Reference standard	EN 12449
Type	singolo
Easy insertion input	No

LOGISTIC


Type of packaging	; box
Customs code	85369010

MATERIAL COMPOSITION AND TREATMENTS

Conductor body material	Electrolitic copper with purity above 99,95%
Minimum thickness of the surface coating of the conducting body	3 μm
Surface treatment of the conductor body	tin plating
Annealing	Yes

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Cable end sleeve [EC000005]
--------------	-----------------------------



tipo	Range of cable cross section [mm²]	Gross weight [g]	L [mm]	C [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	Minimum order quantity [pce]
KE506ST	0.5	0,038	6	1.9	500	50,000	500
KE508ST	0.5	0,048	8	1.9	500	50,000	500
KE7506ST	0.75	0,041	6	2.2	500	40,000	500
KE7508ST	0.75	0,054	8	2.2	500	40,000	500
KE106ST	1	0,050	6	2.4	500	25,000	500
KE110ST	1	0,079	10	2.4	500	25,000	500
KE1508ST	1.5	0,076	8	2.8	500	25,000	500
KE1510ST	1.5	0,092	10	2.8	500	25,000	500
KE2508ST	2.5	0,094	8	3.4	500	20,000	500
KE2510ST	2.5	0,117	10	3.4	500	15,000	500
KE410ST	4	0,182	10	4	500	12,500	500
KE412ST	4	0,215	12	4	500	10,000	500
KE610ST	6	0,236	10	4.7	500	10,000	500
KE612ST	6	0,271	12	4.7	500	7,500	500
KE616ST	6	0,331	15	4.7	500	5,000	500
KE1016ST	10	0,426	15	5.8	250	4,000	250
KE1616ST	10	0,543	15	7.5	250	3,000	250
KE25015ST	25	0,761	15	9.5	100	1,500	100
KE25018ST	25	0,963	18	9.5	100	1,500	100
KE35015ST	35	0,932	16	10.5	100	1,500	100
KE35018ST	35	1,052	18	10.5	100	1,000	100