

F-FP

FEMALE DISCONNECT CONNECTOR, FULLY INSULATED IN POLYCARBONATE, PARTIALLY REINFORCED, FOR COPPER CONDUCTORS, HALOGEN FREE



CERTIFICATIONS & APPROVALS



UL (cULus)

Features

TECHNICAL INFORMATION

Minimum operating temperature	-20 °C
Maximum operating temperature	115 °C
Threshold of operating temperature for short periods	130 °C
Barrel reinforcement ring	Yes
Markings found	factory mark; conductor size-run
Type	singolo
Type of insulation	totale
Easy insertion input	Yes
Self-extinguishing fire class according to UL 94	VO
Reinforced with anti-vibration collar	No

WEIGHT AND DIMENSIONS

Type of connection	A956.0_02
--------------------	-----------

CLASSIFICATION AND DATA ORDERING

ETIM Class 7


Round or flat plug/receptacle [EC000516]

MATERIAL COMPOSITION AND TREATMENTS

Conductor body material	ottone
Minimum thickness of the surface coating of the conducting body	3 µm
Surface treatment of the conductor body	tin plating
Insulated cover material	Polycarbonate PC10500AC
Annealing	No
Halogen free	Yes

LOGISTIC

Type of packaging	; box
Unit in minimal packaging	100 PCE
Minimum order quantity	100 PCE
Customs code	85366990



RF-FP		Insulated cover colour Rosso	Range of cable cross section 0.25 ÷ 1.5 mm²												
tipo	Reference standard	Internal surface of the barrel	Anti-vibration neck material	Tongue width [mm]	Tongue length [mm]	L [mm]	Gross weight [g]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Unit in standard packaging [pce]	
RF-F305P	UL 310; CAN/CSA C22.2 No. 153-14	smooth	copper	3.2	8	20	0,792	4.7	20	4	5.8	2.55	5.2	2,000	
RF-F308P		smooth		3.2	8	20	0,770	4.7	20	4	5.8	2.55	5.2	2,000	
RF-F408P	UL 310; CAN/CSA C22.2 No. 153-14	smooth		5.1	6.4	20	0,903	4.7	20	4	5.8	2.8	5.2	1,500	
RF-F405P	UL 310; CAN/CSA C22.2 No. 153-14	smooth		5.1	6.4	20	0,916	4.7	20	4	5.8	2.8	5.2	1,500	
RF-F608P	UL 310; CAN/CSA C22.2 No. 153-14	smooth	copper	6.8	7.8	22.7	1,300	4.7	22.7	4	6	2.8	5.2	1,000	
BF-FP		Insulated cover colour Blue	Range of cable cross section 1.5 ÷ 2.5 mm²												
tipo	Reference standard	Internal surface of the barrel	Anti-vibration neck material	Tongue width [mm]	Tongue length [mm]	L [mm]	Gross weight [g]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Unit in standard packaging [pce]	
BF-F408P	UL 310; CAN/CSA C22.2 No. 153-14	smooth	copper	5.1	6.4	20	0,962	4.7	20	4.9	6.4	3.4	5.2	1,500	
BF-F608P	UL 310; CAN/CSA C22.2 No. 153-14	groovy	copper	6.8	7.8	23	1,366	4.7	23	4.9	6.8	3.4	5.2	1,000	
GF-FP		Insulated cover colour Yellow	Range of cable cross section 4 ÷ 6 mm²												
tipo	Reference standard	Internal surface of the barrel	Anti-vibration neck material	Tongue width [mm]	Tongue length [mm]	L [mm]	Gross weight [g]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Unit in standard packaging [pce]	
GF-F608P	UL 310; CAN/CSA C22.2 No. 153-14	smooth	copper	6.7	7.8	25.8	2,009	6.5	25.8	6.6	8.1	4.8	7.2	800	