

SACC-M 8FR-3CON-SH - Connector

1436479

<https://www.phoenixcontact.com/us/products/1436479>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Connector, Universal, 3-position, shielded, Socket angled M8, coding: A, Solder connection, knurl material: Brass, nickel-plated, external cable diameter 3.5 mm ... 5 mm



Your advantages

- Safe use in the field, thanks to a high degree of protection
- Reliable signal transmission – 360° shielding in environments with electromagnetic interference

Commercial data

Item number	1436479
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF35
Product key	BF2BJA
Catalog page	Page 18 (C-2-2019)
GTIN	4046356436403
Weight per piece (including packing)	27.1 g
Weight per piece (excluding packing)	26.96 g
Customs tariff number	85366990
Country of origin	DE

SACC-M 8FR-3CON-SH - Connector

1436479

<https://www.phoenixcontact.com/us/products/1436479>



Technical data

Notes

General

NOTE: Observe the permissible bending radii when laying conductors, since the degree of protection may be put in jeopardy if the bending forces are too high. Alleviate mechanical loads upstream of the connector, e.g. by using cable ties.

Mounting

Assembly instructions

The connector pin assignment can be rotated 90° to the cable outlet

Product properties

Product type

Circular connector (cable-side)

Sensor type

Universal

Number of positions

3

No. of cable outlets

1

Shielded

yes

Coding

A

Cable outlet

angled

Insulation characteristics

Overvoltage category


II

Degree of pollution

3

Dimensions

Dimensional drawing



Length

31.9 mm

External dimensions

Outside diameter

3.5 mm ... 5 mm

Housing

Diameter housing

15 mm

Material specifications

Flammability rating according to UL 94

HB

Seal material

NBR

Material of grip body

Brass, nickel-plated

Contact material

CuZn

Contact surface material

Au

SACC-M 8FR-3CON-SH - Connector

1436479

<https://www.phoenixcontact.com/us/products/1436479>



Contact carrier material	PA
Material for screw connection	Brass, nickel-plated

Connection data

Conductor connection

Connection method	Solder connection
Connection cross section	0.08 mm ² ... 0.25 mm ² (flexible)
	0.08 mm ² ... 0.25 mm ² (solid)
Connection cross section AWG	28 ... 24 (flexible)
	28 ... 24 (solid)
Stripping length of the individual wire	3 mm
Tightening torque	0.2 Nm (M8 knurl)

Electrical properties

Rated surge voltage	0.8 kV
Contact resistance	≤ 3 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U _N	48 V AC
	60 V DC
Nominal current I _N	4 A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100
-----------------------------	-------

Connector

Connection 1

Head design	Socket
Head cable outlet	angled
Head thread type	M8
Coding	A

Cable/line

Signal type/category	Universal
Stripping length of the individual wire	3 mm

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-40 °C ... 85 °C (Plug / socket)

Standards and regulations

SACC-M 8FR-3CON-SH - Connector

1436479

<https://www.phoenixcontact.com/us/products/1436479>



M8

Standard designation	M8 connector
Standards/specifications	IEC 61076-2-104

SACC-M 8FR-3CON-SH - Connector


1436479

<https://www.phoenixcontact.com/us/products/1436479>




Drawings

Schematic diagram



Pin assignment M8 socket, 3-pos., view female side

Dimensional drawing



Socket M8 x 1, angled, shielded

SACC-M 8FR-3CON-SH - Connector

1436479

<https://www.phoenixcontact.com/us/products/1436479>



Approvals

ⓘ To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1436479>

UL Listed Approval ID: FILE E 221474				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	60 V	4 A	-	-

cUL Listed Approval ID: FILE E 221474				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	60 V	4 A	-	-

cULus Listed

SACC-M 8FR-3CON-SH - Connector

1436479

<https://www.phoenixcontact.com/us/products/1436479>



Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 9.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SACC-M 8FR-3CON-SH - Connector

1436479

<https://www.phoenixcontact.com/us/products/1436479>



Environmental product compliance

REACH SVHC

Lead 7439-92-1

China RoHS

Environmentally Friendly Use Period = 50 years

For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

SACC-M 8FR-3CON-SH - Connector

1436479

<https://www.phoenixcontact.com/us/products/1436479>



Accessories

PROT-M 8 MS-PA-CHAIN - Screw plug

1430860

<https://www.phoenixcontact.com/us/products/1430860>

M8 sealing cap made of plastic with fixing band for sensor cables, for M8 sockets



SAC-3P-100,0-PUR/SH-0,25 - Cable reel

1526525

<https://www.phoenixcontact.com/us/products/1526525>

By the meter, Cable reel, shielded, PUR halogen-free, black-gray RAL 7021, 3-wire, color single wire: brown, blue, black, cable length: 100 m



SACC-M 8FR-3CON-SH - Connector



1436479

<https://www.phoenixcontact.com/us/products/1436479>

TSD 02 SAC - Torque screwdriver

1208487

<https://www.phoenixcontact.com/us/products/1208487>

Torque screwdriver, with preset torque of 0.2 Nm and 4 mm hexagonal drive for M8 connectors



SACC BIT M8-D12 - Tool

1208474

<https://www.phoenixcontact.com/us/products/1208474>

Nut for assembling M8 connectors with longitudinal knurl and a knurl diameter of 12 mm, for 4 mm hexagonal drive



SACC-M 8FR-3CON-SH - Connector



1436479

<https://www.phoenixcontact.com/us/products/1436479>

TSD-M 1,2NM - Torque screwdriver

1212224

<https://www.phoenixcontact.com/us/products/1212224>



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 0.3 - 1.2 Nm

TSD-M SAC-BIT ADAPTER - Adapter insert

1212600

<https://www.phoenixcontact.com/us/products/1212600>



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits

SACC-M 8FR-3CON-SH - Connector

1436479

<https://www.phoenixcontact.com/us/products/1436479>



WIREFOX SAC - Stripping tool

1212623

<https://www.phoenixcontact.com/us/products/1212623>



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 4.4 to 7 mm, any stripping length

WIREFOX SAC-1 - Stripping tool

1212757

<https://www.phoenixcontact.com/us/products/1212757>



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 3.2 to 4.4 mm, any stripping length

SACC-M 8FR-3CON-SH - Connector

1436479

<https://www.phoenixcontact.com/us/products/1436479>



VS-CABLE-STRIP-VARIO - Stripping tool

1657407

<https://www.phoenixcontact.com/us/products/1657407>

Stripping tool, for the multi-level stripping of shielded cables



Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com