

# Product datasheet

Specifications



## photo-electric sensor - XUM - receiver - 15m - 12..24VDC - M8

XUM2APCNM8R

● Discontinued on: 07 July 2021

! Discontinued

### Main

Range of product	Telemecanique Photoelectric sensors XU
Series name	General purpose single mode
Electronic sensor type	Photo-electric sensor receiver
Sensor name	XUM
Sensor design	Miniature
Detection system	Thru beam
Material	Plastic
Type of output signal	Discrete
Supply circuit type	DC
Wiring technique	3-wire
Discrete output type	PNP
Discrete output function	1 NO or 1 NC programmable
Electrical connection	1 male connector M8, 4 pins
Product specific application	-
Emission	Red thru beam
[Sn] nominal sensing distance	15 m thru beam need a transmitter XUM2AKCNM8T

### Complementary

Enclosure material	PBT
Lens material	PMMA
Output type	Solid state
Add on input	Test by emission breaking
Status LED	1 LED (red) for indicator light 1 LED (green) for instability and supply on
[Us] rated supply voltage	12...24 V DC with reverse polarity protection
Supply voltage limits	10...30 V DC
Switching capacity in mA	<= 100 mA (overload and short-circuit protection)
Switching frequency	<= 1000 Hz

<b>Maximum voltage drop</b>	<3 V (closed state)
<b>Current consumption</b>	13 mA no-load
<b>Maximum delay first up</b>	100 ms
<b>Maximum delay response</b>	0.5 ms
<b>Maximum delay recovery</b>	0.5 ms
<b>Setting-up</b>	Sensitivity adjustment
<b>Depth</b>	20 mm
<b>Height</b>	43 mm
<b>Width</b>	11 mm
<b>Net weight</b>	0.01 kg

## Environment

<b>Product certifications</b>	CE CTick cULus
<b>Ambient air temperature for operation</b>	-30...60 °C
<b>Ambient air temperature for storage</b>	-40...70 °C
<b>Vibration resistance</b>	7 gn, amplitude = +/- 1.5 mm (f = 10...55 Hz) conforming to IEC 60068-2-6
<b>Shock resistance</b>	30 gn (duration = 11 ms) conforming to IEC 60068-2-27
<b>IP degree of protection</b>	IP67 conforming to IEC 60529 IP65 conforming to IEC 60529

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	1.5 cm
<b>Package 1 Width</b>	15 cm
<b>Package 1 Length</b>	15 cm
<b>Package 1 Weight</b>	11 g


## Offer Sustainability

<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	<a href="#">Yes</a>

## Contractual warranty



<b>Warranty</b>	12 months
-----------------	-----------

### Receiver's Dimensions



### Mounting and Clearance

---




- (1) Configuration switch  
(2) Output state LED  
(3) Stability and power on LED

### Connections and Schemes


---


#### M8 Connector



1 : (+)  
3 : (-)  
4 : OUT/Output

#### PNP



**Detection Curves**

(Y) Parallel movement (cm)  
(X) Distance (m)

**Recommended replacement(s)**